



SuperFoam Perforated Anti-Fatigue Mat

Product Specifications

Sku: T17P00xx

- Mat Size:** 2x3 ft, 3x3 ft, 3x4 ft, 3x5 ft, 3x6 ft, 3x8 ft
- Thickness:** 5/8 inch
- Mat Weight:** 2x3 ft 5.34 lbs., 3x3 ft 8.01 lbs., 3x4 ft 10.68 lbs., 3x5 ft 13.35 lbs., 3x6 ft 16.02 lbs., 3x8 ft 21.36 lbs.
- Colors:** Black
- Texture:** Perforated pebble top design surface
- Material:** PVC/Foam
- Weight Loading:** Human foot traffic
- Surfaces Install:** Flat surface, indoor installation
- Shipping:** 2x3 ft - 1 piece per 8x8x25.5 inches box, 24 boxes per pallet
3x3 ft - 1 piece per 8x8x38 inches box, 24 boxes per pallet
3x4 ft - 1 piece per 8x8x38 inches box, 24 boxes per pallet
3x5 ft - 1 piece per 9.25x9.25x38 inches box, 20 boxes per pallet
3x6 ft - 1 piece per 10x10x38.5 inches box, 15 boxes per pallet
3x8 ft – 1 piece per 10x10x38.5 inches box, 15 boxes per pallet

Warranty: 3 Year limited manufacturer’s

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
25% Compression Resistance (psi)	ASTM D1056	6.0 – 12.0
50% Compression Set (%)	ASTM D1056	25 max.
Water Absorption (lb/ft ²)	ASTM D1667	0.1 max.
Tensile Strength (psi)	ASTM D412	90 min.
Surface Flammability/Carpets and Rugs	ASTM D-2859/CPSC FF-170	Pass
Elongation (%)	ASTM D412	100 min.
0 Burn Rate	Flammability, FMVSS302	Pass

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 Toll free: 877-822-6622
 Fax: 715-825-4928
 info@greatmats.com